Amendment to the Claims:

1. (Currently Amended) A positioning method for a radio system, the method comprising:

receiving signals at a unit of the system;

applying at least one test on the received signals prior to processing the signals to select a processing operation on the signals, the operation being one of the following: a correlation processing operation, and a leading edge processing operation; and

then effecting the selected operation selected.

2. (Currently Amended) The method of claim 1, wherein applying the test applied comprises:

determining whether a the signal level of the received signal is above a threshold value.

3. (Currently Amended) The method of claim 2, wherein, when further including:

in response to the level of the received signal is being below the threshold value, selecting the correlation processing operation is selected.

4. (Currently Amended) The method of claim 2 further comprising[[,]]:

when the level of the received signal is above the threshold value, testing whether a the leading edge gradient is above a gradient threshold value.

5. (Currently Amended) The A positioning method of claim 3 for a radio system, the method comprising:

receiving signals at a unit of the system;

applying at least one test on the received signals to select a processing operation on the signals, the operation being one of the following: a correlation processing operation, and a leading edge processing operation; and

then effecting the operation selected;

wherein the test applied comprises determining whether a signal level of the received signal is above a threshold value;

wherein, when the level of the received signal is below the threshold value, the correlation processing operation is selected;

wherein, when ~~the~~ a leading edge gradient is below ~~the~~ a gradient threshold value, the leading edge processing operation is selected.

6. (Currently Amended) The method of claim 4, ~~wherein, when~~further including:

in response to the leading edge gradient ~~is~~ being above the gradient threshold value, selecting the correlation processing operation ~~is selected~~.

7. (Currently Amended) The method of claim 1, comprising:

repeating the test application and operation steps at predetermined intervals.

8. (Currently Amended) The method of claim 1, further comprising:

coherently superposing received pulses before the test application step.

9. (Currently Amended) The method of claim 1 comprising:

convolution of a pulse with a bump function.

10. (Currently Amended) The method of claim 1, further comprising[[,]]:

~~when the~~in response to a signal level ~~is~~ being below ~~a~~ ~~the~~ signal level threshold, extending a receiving time period for the signal and applying the at least one test again.

11. (Currently Amended) The method of claim 1, further comprising[[,]]:

before testing whether a the leading edge gradient is above a threshold value, reducing a the next transmit period.

12. (Currently Amended) The method according to claim 1, further comprising:

reducing a the time period for a the leading edge test for operation in a power-saving mode.

13. (Currently Amended) The method according to claim 1, further comprising:

effecting the leading edge processing operation after selection with no intermediate testing or processing.

14. (Currently Amended) The method according to claim 1 comprising measuring the a gradient using the formula:

$i = Cdv/Dt$

Where, V=voltage of the a signal waveform,

C=capacitance,

i=current, and

t=time.

15. (Currently Amended) The method according to claim 1 wherein the leading edge processing operation comprises:

differentiating the a received signal voltage or peak and locating the a zero-crossing (point of inflexion).

16. (Currently Amended) A computer program product directly loadable into the a internal memory of a digital computer, comprising:

software code portions for controlling the digital computer to perform performing the method of claim 1 when said product is run on a computer.

17. (Currently Amended) A ~~computer program embodied on a computer-readable medium and directly loadable into the internal memory of a digital computer, comprising~~carrying software code ~~portions~~for controlling a computer to perform ~~performing~~ the method of claim 1 when said ~~program~~software code is run on ~~a~~the computer.

18-19. (Cancelled)

20. (Currently Amended) A positioning apparatus for a radio system, the apparatus comprising:

a receiver means to receive radio frequency signals ~~at a unit of the system~~which have potentially suffered at least one of noise degradation and multi-path degradation in a propagation environment;

testing means ~~to apply at least one test~~for testing ~~on~~ the received radio frequency signals for at least noise degradation and multi-path degradation and selecting ~~to select a processing operation on the signals which~~ from among the ~~following:~~ a correlation processing operation[[,]] and a leading edge processing operation based on the testing; and

a processing means ~~to effect the operation selected~~ for subsequently processing the tested radiofrequency signals with the selected one of the correlation based processing operation and the leading edge processing operation.

21. (Currently Amended) The apparatus of claim 20, wherein the testing means includes: ~~comprising~~

means to determine whether a ~~the~~signal level of the received radio frequency signal is above a threshold value.

22. (Currently Amended) The apparatus of claim 21, wherein the testing means includes: ~~comprising~~

means ~~to select~~which selects the correlation processing operation ~~when~~in response to the signal level of the received signal ~~is~~being below the level threshold value.

5

23. (Currently Amended) The apparatus of claim 22, wherein the testing means includes: ~~comprising~~

means to test signals with signal level above the level threshold value to determine whether the signal has a leading edge gradient ~~is~~above a gradient

5   threshold value~~, when the level of the received signal is above the threshold value~~.

24. (Currently Amended) The apparatus of ~~claim 22 comprising~~claim 23, wherein the testing means includes:

means ~~to select~~ which selects:

the leading edge processing operation[[,]] ~~when~~ in response to the

5   leading edge gradient ~~is~~being below the gradient threshold value, and

the correlation processing operation in response to the leading edge gradient being above the gradient threshold value.

25. (Cancelled)

26. (Currently Amended) The apparatus of any of claim 20, ~~comprising~~ wherein the testing means includes:

means to cause the testing means to repeat the test~~ing application and operation steps~~ at predetermined intervals.

27. (New) The method of claim 3, further including;

when the level of the received signal is above the threshold value, testing whether a leading edge gradient is above a gradient threshold value;

in response to the leading edge gradient value being below the gradient
5   threshold value, performing the leading edge processing operation on the signal;

response to the leading edge being above the gradient threshold value, performing the correction processing operation on the signal.